Application No.: 10/523,003

RECEIVED

Docket No.: 4590-372

CENTRAL FAX CENTER

AUG 2 1 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 4. (new) An antenna for a sonar with synthetic antenna processing, comprising:
- a plurality of spaced out sensors distributed in a main zone in which the sensors are spaced out by a pitch d and at least in one zone located at one end of the antenna in which the sensors are spaced out by a pitch d' smaller than pitch d, said pitch d being defined so as to obtain the desired level of the grating lobe in the directivity pattern of a channel and said pitch d' being defined so as to obtain the desired precision for the self-calibration of the antenna, said self-calibration being made by the means of an inter-recurrences correlation.
- 5. (new) The antenna according to claim 4, in which the pitch d between sensors is reduced to d' at both end zones of the antenna with regard to said main zone.
- 6. (new) The antenna according to claim 4, in which the pitch d between sensors is reduced to d' at only one end zone of the antenna with regard to said main zone.
- 7. (new) The antenna according to claim 4, in which the pitch d is defined by the following formula:

$$d \approx 0.7 \cdot \lambda/\Delta\theta$$

in which λ represents the wavelength of the signal and θ the bearing width of the transmission sector.

8. (new) The antenna according to claim 7, in which the pitch d' is determined so that the report d/d' is at least greater than 1.5.

Application No.: 10/523,003

Docket No.: 4590-372

- 9. (new) The antenna according to claim 8, in which the pitch d between sensors is reduced to d' at both end zones of the antenna with regard to said main zone.
- 10. (new) The antenna according to claim 8, in which the pitch d between sensors is reduced to d' at only one end zone of the antenna with regard to said main zone.